

LATMB patreizējie resursi



Fluke 734C (7004N)

Līdzsprieguma avots (DC voltage standard)

Uncertainty limit $\pm 1,5$ ppm ($15\mu\text{V}$ @ 10VDC)
LATMB standarta nenoteiktība $5\mu\text{V}$ @ 10VDC)

Pretestības spoles

$1\ \Omega \pm 10$ ppm ($\pm 10\ \mu\Omega$)
 $10\text{k}\Omega \pm 2$ ppm ($\pm 20\ \mu\Omega$)



Fluke 5730A-7003
Low thermal test lead set

Fluke 8508A (8588A)
8,5 dig multimetrs



Nepieciešams iegādāties

Fluke 5730A
Kalibrators



Fluke 5730A
Kalibrators

Izmanto tikai 3 artefaktus (līdzsprieguma avotu, $1\ \Omega$ un $10\ \text{k}\Omega$ pretestības spoles), lai nokalibrētu (neregulētu) visu kalibratora darbības diapazonu

Var piemērot 24h specifikāciju

Klientu mērinstrumentu kalibrēšana

MULTIMETRI

Fluke 8508A (8588A)
6,5
7,5
8,5 dig multimetrs
Piem., Fluke 8508A

Var piemērot 24h vai 90 dienu specifikāciju



KALIBRATORI

Visi pārējie industrijā sastopamie kalibratori
Piem., Transmille 3010 vai 4010
Fluke 55XX kalibratori

